



Openload Package

Connect to the Openload File Sharing API to upload, share and edit any file. Test an API call in your browser and export the code snippet into your app.

- Domain: openload.co
- Credentials: login, key

How to get credentials:

1. Sign in openload.co
2. You can find credentials in the User Panel at the "User Settings" Tab



Openload.getAccountInfo

Everything account related (total used storage, reward)

| Field | Type | Description |
|-------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |



Openload.preparingDownload

Preparing a Download

| Field | Type | Description |
|--------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| fileId | String | File-ID |



Openload.getDownloadLink

Get a download link by using download ticket

| Field | Type | Description |
|-----------------|--------|--------------------------------------|
| fileId | String | File-ID |
| ticket | String | Previously generated download ticket |
| captchaResponse | String | Result of the captcha |



Openload.checkFileStatus

Check the status of a file, e.g. if the file exists

| Field | Type | Description |
|--------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| fileId | String | File-ID |



Openload.uploadFile

File upload

| Field | Type | Description |
|----------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| file | File | Uploaded file |
| folderId | String | Folder-ID to upload to |



Openload.uploadFileRemotely

Remote Uploading a file

| Field | Type | Description |
|----------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| url | File | Remote URL |
| folderId | String | Folder-ID to upload to |



Openload.checkRemoteUploadStatus

Check Status of Remote Upload

| Field | Type | Description |
|-------|-------------|------------------------------------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| id | String | Remote Upload ID |
| limit | String | Maximum number of results (Default: 5, Maximum: 100) |



Openload.showFoldersContent

Shows the content of your folders

| Field | Type | Description |
|----------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| folderId | String | Folder-ID |



Openload.renameFolder

Set a new name for a folders

| Field | Type | Description |
|----------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| folderId | String | Folder-ID |
| name | String | new Folder-Name |



Openload.renameFile

Set a new name for a file

| Field | Type | Description |
|--------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| fileId | String | File-ID |
| name | String | new File-Name |



Openload.convertFiles

Convert previously uploaded files to a browser-streamable format (mp4 / h.264)

| Field | Type | Description |
|--------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| fileId | String | File-ID |



Openload.getRunningFileConverts

Shows running file converts by folder

| Field | Type | Description |
|----------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| folderId | String | Folder-ID |



Openload.getVideoThumbnail

Shows the video splash image (thumbnail)

| Field | Type | Description |
|--------|-------------|------------------------|
| login | credentials | API-Login |
| key | credentials | API-Key / API-Password |
| fileId | String | File-ID |